



Sales Specification

Sodium Chlorite (NaClO₂)

Technical Dry

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Sodium Chlorite, wt% as NaClO ₂	77.5 - 82.5
Sodium Chlorate, wt% as NaClO ₃	4 max.
Sodium Chloride, wt% as NaCl	11 - 19
Sodium Hydroxide, wt% as NaOH	3 max.
Sodium Carbonate, wt% as Na ₂ CO ₃	2 max.
Sodium Sulfate, wt% as Na ₂ SO ₄	3 max.
Hydrogen Peroxide, wt% as H ₂ O ₂	0.01 max.
Water (by difference), wt%	6 max.
Arsenic, ppm	3 max.
Lead, ppm	10 max.
Heavy Metals as Pb, ppm	20 max.
Mercury, ppm	0.1 max.

NSF listed, NSF/ANSI Standard 60 (Wichita, KS/ Fairmont City, IL, Sauget, IL)
Meets requirements of ANSI/AWWA B303-18

EPA Reg. No: 5382-42

CONTAINERS:

Drums - 100 pounds net

Form#: 610 10/2018



14555 Dallas Parkway, Suite 400
Dallas, TX 75254
800-221-6514

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.