SAFETY DATA SHEET



METHYLENE CHLORIDE, DECAFFEINATION GRADE

North America EN SDS No.: M47007

Rev. Date: 23-Jun-2023 **Rev. Num.** 01

SECTION 1. CHEMICAL PRODUCT / COMPANY IDENTIFICATION

Company Identification:	Occidental Chemical Corporation 14555 Dallas Parkway, Suite 400 Dallas, Texas 75254-4300		
24-Hour Emergency Telephone Number:	1-800-733-3665 (USA); CANUTEC (Canada): 1-613-996-6666; CHEMTREC (within USA and Canada): 1-800-424-9300; CHEMTREC (outside USA and Canada): +1 703-527-3887; CHEMTREC Contract No: CCN16186		
To Request an SDS:	MSDS@oxy.com or 1-972-404-3245		
Customer Service:	1-800-752-5151 or 1-972-404-3700		
Product Identifier:	METHYLENE CHLORIDE		
Trade Name:	Methylene Chloride, Decaffeination Grade		
Synonyms:	Dichloromethane; Methylene Dichloride		
Product Use:	Solvent decaffeination		
Uses Advised Against:	NOT FOR USE IN BATHTUB STRIPPING APPLICATIONS. NOT FOR USE IN RESIDENTIAL HOME OR WORKSHOP AREAS. NOT FOR ANY COMMERCIAL APPLICATIONS TAKING PLACE IN RESIDENTIAL SETTINGS. NOT FOR USE IN COMMERCIAL/INDUSTRIAL APPLICATIONS NOT PROPERLY VENTILATED OR NOT DESIGNED TO ACCOMMODATE THE SAFE USE OF THIS CHEMICAL*.		
*NOTE: ALL COMMERCIAL/INDU REMOVAL, SHOULD COMPLY W OSHA'S METHYLENE CHLORIDE	STRIAL USES OF METHYLENE CHLORIDE, INCLUDING PAINT AND COATING ITH ALL RISK MANAGEMENT MEASURES FOUND IN 29CFR 1910.1052, E REGULATIONS (REGARDLESS OF EMPLOYER SIZE).		
Restrictions on Use (United States):	This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.		

SDS No.: M47007 Supersedes Date: New SDS	Rev. Date: 23-Jun-2023 Rev. Num. 01
Restrictions on Use (EU):	In accordance with ANNEX XVII to REACH (Conditions of restriction) - Methylene Chloride shall not be placed on the market, or used, as substances or as constituents of other substances, or in mixtures in concentrations equal to or greater than 0.1% by weight, where the substance or mixture is intended for use in paint strippers. Restricted to industrial use and to professionals approved in certain EU Member States - verify where use is allowed.
Other Global Restrictions on Use:	Methylene Chloride may be restricted and/or prohibited for use in cosmetic products. See local, regional, and/or national regulations specific to cosmetic regulations. Other restrictions on use based on local, regional, or national regulations may exist and must be determined on a case-by-case basis.
Chemical Family:	Saturated aliphatic halogenated solvent
Note:	The Decaffeination Grade product contains small amounts of stabilizer, which does not impact the hazard classification of the final product.

SECTION 2. HAZARDS IDENTIFICATION

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

EMERGENCY OVERVIEW:

Color:	Colorless
Physical State:	Liquid
Appearance:	Clear
Odor:	Chloroform-like odor

Signal Word:

DANGER

MAJOR HEALTH HAZARDS: HARMFUL IF SWALLOWED. MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. SUSPECTED OF CAUSING GENETIC DEFECTS. MAY CAUSE CANCER. CAUSES DAMAGE TO CARDIOVASCULAR SYSTEM INCLUDING ELEVATED CARBOXYHEMOGLOBIN LEVELS. MAY CAUSE DAMAGE TO LIVER THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENTS: Obtain, read, and follow all safety instructions before use. Do not breathe mist, vapors, or spray. Wash hands and exposed skin and clothing thoroughly after handling. Do not touch eyes. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye, and face protection.

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

ADDITIONAL HAZARD INFORMATION: Exposure in an enclosed or poorly ventilated area may be very harmful. Methylene chloride can be metabolized to carbon monoxide (CO), which is then very tightly bound to hemoglobin. This complex is called carboxyhemoglobin (COHb) and results in a reduction in the oxygen carrying capacity of the blood. This product may be absorbed through the skin, causing systemic effects.

HAZARD CLASSIFICATION:

GHS: CONTACT HAZARD - SKIN:	Category 2 - Causes skin irritation		
GHS: CONTACT HAZARD - EYE:	Category 2A - Causes serious eye irritation		
GHS: ACUTE TOXICITY - ORAL:	Category 4 - Harmful if swallowed		
GHS: TARGET ORGAN TOXICITY (SINGLE	- Category 1 - Causes damage to cardiovascular system		
EXPOSURE):	including elevated carboxyhemoglobin levels		
	 Category 3 - May cause drowsiness or dizziness 		
HS: TARGET ORGAN TOXICITY (REPEATED Category 2 - May cause damage to liver through			
EXPOSURE):	prolonged or repeated exposure		
GHS: CARCINOGENICITY:	Category 1B - May cause cancer		
GHS: GERM CELL MUTAGENICITY:	Category 2 - Suspected of causing genetic defects		
HAZARDS NOT OTHERWISE CLASSIFIED (HNOC):	- ASPIRATION HAZARD - CATEGORY 2: May be harmful		
	if swallowed and enters airways		

GHS SYMBOL: Exclamation mark, Health hazard



GHS HAZARD STATEMENTS:

GHS - Health Hazard Statement(s)

- Harmful if swallowed
- Causes skin irritation
- Causes serious eye irritation
- May cause drowsiness or dizziness
- Suspected of causing genetic defects
- May cause cancer
- Causes damage to cardiovascular system including elevated carboxyhemoglobin levels
- · May cause damage to Liver through prolonged or repeated exposure

Additional Hazards - GHS Hazards Not Otherwise Classified (HNOC):

• ASPIRATION HAZARD - CATEGORY 2: May be harmful if swallowed and enters airways

GHS - Precautionary Statement(s) - Prevention

- Obtain, read, and follow all safety instructions before use
- Do not breathe mist, vapors, or spray

SDS No.:	M47007	
Supersede	es Date:	New SDS

Rev. Date: 23-Jun-2023 **Rev. Num.** 01

- · Wash hands and exposed skin and clothing thoroughly after handling. Do not touch eyes
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection/hearing protection

GHS - Precautionary Statement(s) - Response

- IF SWALLOWED: Get emergency medical help immediately
- Rinse mouth
- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation occurs: Get medical help
- Take off contaminated clothing and wash it before reuse

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

- If eye irritation persists: Get medical help
- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- IF INHALED: Get medical help if you feel unwell
- IF exposed or concerned: Get emergency medical help immediately
- Specific treatment (see "Notes to Physician" in Section 4 of the SDS)

GHS - Precautionary Statement(s) - Storage

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up

GHS - Precautionary Statement(s) - Disposal

• Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations

Health Hazards of Significance Not Mentioned in GHS Classification

• Methylene chloride can be metabolized to carbon monoxide (CO), which is then very tightly bound to hemoglobin. This complex is called carboxyhemoglobin (COHb) and results in a reduction in the oxygen carrying capacity of the blood

• Exposure in an enclosed or poorly ventilated area may be very harmful

• May cross the placenta. May be excreted in breast milk; however, there were no indications of neonatal toxicity due to exposure of the parenteral group to Methylene Chloride during gestation and lactation.

. This material may be absorbed across the skin causing systemic effects

Additional Hazard Information

Methylene chloride is listed on The Endocrine Disruptors Exchange's (TEDX) List of Potential Endocrine Disruptors (ED) database of chemicals with the potential to affect the endocrine system. Every chemical on the TEDX List has one or more verified citations published, accessible, primary scientific research demonstrating effects on the endocrine system. Literature data concerning reproductive/developmental effects points out directly to a potential ED-like mode of action. In particular, taking into account both: i) the CYP-mediated mechanism(s) supporting both hepatic and biliary tract carcinogenesis alert at low dichloromethane doses, and ii) the CYP2E1-mediated mechanism supporting the reproductive/developmental alert in the male germ line, a concern on the possibility that dichloromethane could act via an ED-like mechanism exists. A study (Mennear JH et al., 1988) on dichloromethane-mediated carcinogenesis in F344/N rats indicated that a set of endocrine-regulated tissues (mammary glands, testis, adrenals) were responding, in a non-linear dose-dependent manner, to the treatment with dichloromethane, suggesting a possible relationship with disturbed endocrine function and raising the possibility of a hormonal-mediated mechanism(s) at a realistic scenario of exposure to humans.

PBT and vPvB assessment:

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

The overall conclusions - based on the available data under EU REACH registration- of the preliminary PBT assessment are that the (screening) criteria for PBT/vPvB are not met and that further testing in the scope of the final PBT assessment is not considered to be required

Component	U.S CERCLA/SARA - Section 313 - PBT Chemical Listing	EU - PBT / vPvB Status
Methylene chloride (Dichloromethane)	Not listed	Considered NOT to be an EU PBT

Endocrine Disruptor Assessment:

This substance is currently under evaluation in an EU legislative process due to explicit concerns for possible endocrine disrupting properties. Methylene Chloride is listed on The Endocrine Disruptors Exchange's (TEDX) List of Potential Endocrine Disruptors database of chemicals with the potential to affect the endocrine system. Every chemical on the TEDX List has one or more verified citations published, accessible, primary scientific research demonstrating effects on the endocrine system.

Component	Endocrine Screening List
Methylene chloride (Dichloromethane)	TEDX Potential Endocrine List: Present US EPA Endocrine Final Screening List: Present
	(SDWA chemical) Japan EXTEND List: Not Currently Tested

See Section 11: TOXICOLOGICAL INFORMATION

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Systematic Chemical Name	Common name	CAS Number	Percent [%]
Methylene chloride (Dichloromethane)	Dichloromethane	Methylene Chloride	75-09-2	> 99.99

SECTION 4. FIRST AID MEASURES

<u>EYE CONTACT:</u> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help.

<u>SKIN CONTACT</u>. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical help. Take off contaminated clothing and wash it before reuse. Specific treatment (see "Notes to Physician" in Section 4 of the SDS below).

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

INHALATION: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF INHALED: Get medical help if you feel unwell. Specific treatment (see "Notes to Physician" in Section 4 of the SDS below).

INGESTION: IF SWALLOWED: Get emergency medical help immediately. Rinse mouth. Specific treatment (see "Notes to Physician" in Section 4 of the SDS below).

Most Important Symptoms/Effects (Acute and Chronic [Delayed]):

Acute Symptoms/Effects:

Eye: Eye Irritation. Mild eye irritation may occur when exposed to vapor. Splash of liquid in the eye can cause conjunctival irritation and burning pain. Prolonged contact can cause severe corneal burns.

Skin: Skin Irritation. Skin exposure may cause intense burning sensation, mild redness and numbness. Severe burns may develop following prolonged exposures. Will remove the natural greases resulting in dryness, cracking and dermatitis. Repeated and/or prolonged skin contact may cause reddening, burning and blisters.

Inhalation (Breathing): Respiratory System Effects: Pulmonary irritation, cough, chest discomfort, shortness of breath, headache, euphoria, nausea and vomiting, respiratory irritation. Changes in heart rate, paresthesias, sleepiness and seizures are described. Heavy exposure can result in muscle weakness or hypotonia, syncope, stupor followed by loss of consciousness. Complications include cardiac abnormalities and elevations of carboxyhemoglobin. Coma with respiratory depression may result in death.

Ingestion (Swallowing): Ingesting this material may cause nausea, vomiting, mucosal irritation with burning sensation. System effects include central nervous system depression, headache, syncope, seizures, and coma. Ingesting concentrated solutions of this material can cause corrosion of the GI tract and perforation. The minimum oral lethal dose is estimated at 0.5 to 5 ml/kg. Lesser amounts may cause significant toxicity.

Chronic (Delayed) Symptoms/Effects:

May cause cancer. Repeated or prolonged exposure may cause blood and liver damage. Suspected of causing genetic defects.

Target Organ Effects: Liver.

Protection of First-Aid Responders: Protect against vapor/gas exposure. Protect against liquid contamination. Most cases of serious toxicity or death have been associated with stripping operations and or use in enclosed spaces.

Notes to Physician:

There is no antidote. If the skin was in prolonged contact with liquid methylene chloride, chemical burns may result; treat as thermal burns. The primary exposure route is inhalation. Acute symptoms from low airborne levels are generally mild and self-limiting following removal from exposure and should require no specific treatment. The primary toxicity is central nervous system depression. Administer supplemental oxygen by mask to patients who have symptoms. Hypotension may respond to fluid replacement or management of underlying cardiac rhythm disorder.. Methylene chloride is metabolized to carbon monoxide. Carbon monoxide levels may increase after exposure has ceased. It is unlikely that the carbon monoxide produced from methylene chloride metabolism will justify hyperbaric oxygen therapy; however, 100% oxygen at normal pressure is a useful treatment. The comparative efficacy of 100% normobaric oxygen compared with that of hyperbaric oxygen has not been definitively studied. May cause cardiac arrhythmias. Treatment with non-catecholamine agent is theoretically preferred. Treat seizures with benzodiazepines. Active management of metabolic acidosis and associated electrolyte abnormalities may be required if they are severe, slow to resolve or accompanied by significant complications. Treat patients who have bronchospasm with aerosolized bronchodilators. The use of bronchial sensitizing agents in situations of multiple chemical exposures may pose additional risks. Consider the health of the myocardium before choosing which type of bronchodilator should be administered. Cardiac sensitizing agents may be appropriate; however, the use of cardiac sensitizing agents after

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

exposure to certain chemicals may pose enhanced risk of cardiac arrhythmias (especially in the elderly). If ingested, do not induce emesis. For ingestion, protect the airway and do not administer fluids or attempt to decontaminate due to the risk of vomiting and aspiration. Protect the airway. May dissolve some medical grade plastics.

Interaction with Other Chemicals Which Enhance Toxicity: May potentiate other agents that cause central nervous system (CNS) and respiratory system depression, such as alcohol, opiates.

Medical Conditions Aggravated by Exposure: May increase potential for cardiac arrhythmia. May increase carboxyhemoglobin levels. May worsen respiratory system disorders such as asthma and other breathing disorders. May worsen central nervous system disorders such as seizure disorders or impair central nervous system functions. May worsen ischemic heart disease.

SECTION 5. FIRE FIGHTING MEASURES

Fire Hazard: Slight fire hazard. This material may burn, but does not readily ignite.

Explosive properties: It will not form explosive mixtures with air at ordinary temperatures. Closed containers may explode or rupture when exposed to extreme heat (fire).

Extinguishing Media: Use foam, dry chemical, CO2, or water spray.

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

Fire Fighting: Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Concentrated vapors may be ignited by high intensity source. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Flood with fine water spray. Do not scatter spilled material with high-pressure water streams. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Keep water runoff out of water supplies and sewers (see Section 6 of the SDS).

Advice for Firefighters: Firefighters must wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face mask operating in positive pressure mode. Concentrated vapors may be ignited by high intensity source. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Flood with fine water spray. Do not scatter spilled material with high-pressure water streams. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Keep water runoff out of water supplies and sewers (see Section 6 of the SDS).

Component	Immediately Dangerous to Life/ Health (IDLH)
Methylene chloride (Dichloromethane)	2300 ppm IDLH
75-09-2	

Hazardous Combustion Products: Hydrogen chloride; Chlorine; Phosgene; Oxides of carbon

Products Formed During Combustion and Thermal Degradation: Hydrogen chloride; Chlorine; Phosgene; Oxides of carbon

Sensitivity to Mechanical Impact: Not sensitive.

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

Sensitivity to Static Discharge:	Not sensitive.	
Lower Flammability Level (air):	12% @ 100°C	
Upper Flammability Level (air):	19% @100°C	
Flash point:	None	
Auto-ignition Temperature:	1033 °F (556.1 °C)	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Most vapors are heavier than air and will spread along ground and collect in low or confined areas (drains, basements, tanks). Do not breathe vapors, mist, or spray. Ventilate closed spaces before entering. Exposure in an enclosed or poorly ventilated area may be very harmful. Keep unnecessary people away, isolate hazard area and deny entry. Evacuation of surrounding area may be necessary for large spills. Shut off ventilation systems to occupied areas that may be impacted by vapors picked up by the intake systems. Do not get in eyes, on skin or on clothing.

Personal Protective Equipment: See Section 8 for information on personal protective equipment.

Emergency Procedures: If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply. Stop leak if possible without personal risk. Evacuate unnecessary personnel and eliminate all sources of ignition. Shut off ventilation systems to occupied areas that may be impacted by vapors picked up by the intake systems. Before entering tanks or opening service lines that may have contained chlorinated organics, they should be completely emptied, purged, and checked for vapors before performing maintenance activities. Never enter a confined space (which includes tanks or pits) without following proper entry procedures such as 29 CFR 1910.146.

Environmental Precautions: Keep out of water supplies, sewers, and soil. Avoid discharge into drains, surface water or groundwater. Releases should be reported, if required, to appropriate regulatory agencies.

Methods and Materials for Clean-up

Recovery: Reuse or reprocess, if possible. Completely contain spilled materials with dikes, sandbags, etc. Collect with appropriate absorbent and place into suitable container. Keep container tightly closed. Liquid material may be removed with a properly rated vacuum truck.

Neutralization: Absorb spilled liquids into compatible absorbent materials and place into sealed containers. **Final Disposal:** It may be necessary to contain and dispose of methylene chloride as a Hazardous Waste. Contact your state department of Environmental Protection or your reginal office of the federal Environmental Protection Agency (EPA) for specific recommendations. For waste disposal, see section 13.

<u>Additional Disaster Prevention Measures</u>: Potential methylene chloride exposures have special United States OSHA requirements as noted in CFR 1910.1052.

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

SECTION 7. HANDLING AND STORAGE

Handling:

Precautions for Safe Handling: Obtain, read, and follow all safety instructions before use. Do not breathe gas, vapors, or spray mist. Most vapors are heavier than air and will spread along ground and collect in low or confined areas (drains, basements, tanks). Avoid contact with skin, eyes, and clothing. Wear personal protective equipment as described in Exposure Controls/Personal Protection (Section 8) of the SDS. Wash hands and exposed skin and clothing thoroughly after handling. Do not touch eyes. Wash thoroughly with soap and water after handling. Do not eat, drink, or smoke in areas where this material is used. Use only outdoors or in a well-ventilated area.

Technical measures/precautions: Recommended transfer of chlorinated organics is by pump with special precautions to not allow moisture or atmospheric air into the (un)loading lines. Transport and (un)loading should be done under nitrogen blanket to exclude moisture. If moisture could enter into the tank via seals or valves, it should be blanketed by slight overpressure of nitrogen. Use of air for blanketing might contain water and other impurities that lead to solvent degradation/acidification.

Other precautions: A number of important safety devices should be incorporated to warn of equipment failures and to avoid damages. Their purpose is specially to prevent leakage of product and they include: containment to collect drips and leaks, leakage indicators, liquid level indicators, exhaust installations, high level trip and high- and low- level alarms.

Prevention of contact: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors, or spray. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, footwear, clothing, eye, and face protection.

Storage:

Safe Storage Conditions: Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Store in a cool, dry area. Store in a well-ventilated area. Prevent water or moist air from entering storage tanks or containers. Do not enter confined spaces unless adequately ventilated. Do not store in aluminum container or use aluminum fittings or transfer lines. To minimize the decomposition of dichloromethane, storage containers should be galvanized or lined with a phenolic coating. Protect from sunlight. Do not reuse drum without recycling or reconditioning in accordance with any applicable federal, state, or local laws. Do not use cutting or welding torches, open flames, or electric arcs on empty or full containers. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

Technical measures: Chlorinated organics and the vapors should always be contained in suitably designed tanks and pipes constructed of compatible materials that have been well maintained and in good condition. Secondary containment should be designed with compatible materials that can hold 110% of the largest expected amount of stored product. Aluminum, non-compatible plastics, or fiberglass reinforced plastic are prohibited for use in chlorinated organic service. For more information about incompatible products or storage requirements, please contact the OxyChem Technical Service Group at OxyChem_Tech_Service@oxy.com.

Incompatible Substances: Bases. Amines. Alkali metals. Methylene chloride reacts with strong oxidizers, caustic substances, chemically active metals such as aluminum, magnesium, potassium, sodium, and concentrated nitric acid.

Packaging or Materials of Construction: Carbon steel of welded construction is the usual material for storage and

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

handling of chlorinated solvents in bulk tanks. If rust contamination cannot be tolerated, an appropriate grade of stainless steel may be preferred; hot-dip galvanized steel (though not steel galvanized by electroplating or spraying) should be suitable, or a coating may be applied to the steel. A certificate of the suitability of the coating should be obtained from the supplier/manufacturer. Aluminum, magnesium, and their alloys should not be used in chlorinated solvents service. Plastics are not generally suitable for bulk chlorinated solvents service.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

REGULATORY EXPOSURE LIMIT(S):

Listed below for the product components that have regulatory occupational exposure limits (OEL's) established. See 29 CFR 1910.1052 (OSHA's regulatory standard for Methylene Chloride) for additional requirements when 8-hour action level (12.5 ppm TWA) is exceeded.

Component	OSHA Final PEL TWA	OSHA Final PEL STEL	OSHA Final PEL Ceiling
Methylene chloride	25 ppm (TWA)	125 ppm { STEL} see 29	
(Dichloromethane)		CFR 1910.1052	
75-09-2 (> 99.99 %)			

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

Component	Canada - TWAs	Canada - STELs	Canada - Ceilings
Methylene chloride	Ontario - 50 ppm (TWA)		
(Dichloromethane)	Alberta - 50 ppm (TWA)		
75-09-2 (> 99.99 %)	Alberta - 174 mg/m3 (TWA)		
	British Columbia - 25 ppm		
	(TWA)		

NON-REGULATORY EXPOSURE LIMIT(S):

Listed below are the product components that have advisory (non-regulatory) occupational exposure limits (OEL's) established.

Component	ACGIH	ACGIH	ACGIH	Skin	NIOSH	AIHA	OSHA	OSHA	OSHA
	TWA	STEL	Ceiling	Absorptio	RELs	WEELs	TWA	STEL	Ceiling
				n - ACGIH			(Vacated)	(Vacated)	(Vacated)
Methylene	50ppm			Not Listed			500 ppm	2000 ppm	1000 ppm
chloride	TWA								
(Dichloromethan									
e)									
75-09-2 (>									
99.99 %)									

- The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

ENGINEERING CONTROLS: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits. Monitoring should be performed regularly in accordance with 29 CFR 1910.1052(d) to determine exposure level(s).

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear safety glasses with side-shields. Wear chemical safety goggles and/or a face-shield to protect against skin and eye contact when appropriate. Provide an emergency eyewash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear chemical resistant clothing and footwear to prevent skin contact.

Hand Protection: Wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove. The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors like other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Protective Material Types: Trellchem®. Tychem®. Viton®. Polyvinyl alcohol (PVA). Ethyl vinyl alcohol laminate ("EVAL").

Respiratory Protection: Because methylene chloride may cause eye irritation or damage, the OSHA standard for methylene chloride (29 CFR 1910.1052) prohibits use of quarter and half mask respirators; additionally, only supplied air respirators (SARs) can be used for other than emergency escape purposes because methylene chloride may pass through air purifying respirators. Respiratory protection requirements for methylene chloride are in 29 CFR 1910.1052(g). When concentrations are above the IDLH, or are unknown, or during spills and/or emergencies, use any supplied-air respirator that has a facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Component	Immediately Dangerous to Life/ Health (IDLH)
Methylene chloride (Dichloromethane)	2300 ppm IDLH
75-09-2 (> 99.99 %)	

Other Protective Equipment: Provide an emergency eyewash fountain and quick drench shower in the immediate work area.

HYGIENE MEASURES: Obtain, read and follow all safety instructions before use. Do not breathe mist, vapors, or spray. Wash hands and affected skin immediately after handling, before breaks, and at the end of the workday. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye, and face protection.

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Color: Odor: Odor Threshold [ppm]: pH: **Melting Point/Range:** Freezing Point/Range: **Boiling Point °C** Flash point: Evaporation Rate (ether=1): Lower Flammability Level (air): **Upper Flammability Level (air):** Vapor Pressure: Water Solubility: Vapor Density (air=1): Relative Density/Specific Gravity (water=1): Partition Coefficient (n-octanol/water): Auto-ignition Temperature: Viscosity: **Dynamic viscosity: Kinematic viscosity** Molecular Weight:

Other Information Chemical Family: Volatility: Surface tension:

Liquid Colorless Chloroform-like odor 200-300 ppm (causes olfactory fatigue) Not applicable -139 °F (-95 °C) -139 °F (-95 °C) 103.5 °F (39.7 °C) None 0.7 12% @ 100°C 19% @100°C 350 mmHg @ 20°C and 435 mmHg @ 25°C 1.32% @ 25 C or 13,000 mg/l at 25 °C 2.931.31 - 1.32 @ 25°C $\log Kow = 1.25$ 1033 °F (556.1 °C) - 0.41 (cps) @ 77°F 0.42 mPa s @ 298.15 K 0.9 Centistokes @ 20°C 84.94

Saturated aliphatic halogenated solvent 100% by volume 28.12 dyne/cm @ 20°C

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal temperatures and pressures.

<u>Reactivity:</u> Reacts violently with active metals.

Possibility of Hazardous Reactions: Avoid heat, flames, sparks, and other sources of ignition. Containers may rupture or explode if exposed to heat. Reacts violently with active metals. Avoid contact with incompatible substances and conditions due to generation of phosgene and other toxic and irritating substances.

<u>Conditions to Avoid (e.g., static discharge, shock, or vibration)</u>: Methylene chloride dissolves endothermically in concentrated nitric acid to give a detonable solution.

Incompatible Substances: Bases. Amines. Alkali metals. Methylene chloride reacts with strong oxidizers,

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

caustic substances, chemically active metals such as aluminum, magnesium, potassium, sodium, and concentrated nitric acid.

Hazardous Decomposition Products: Hydrogen chloride, Chlorine, Phosgene, Oxides of Carbon.

Hazardous Polymerization: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS:

TOXICITY:

Dermal exposure results in absorption but at a slower rate than via the oral or inhalation routes of exposure.

ACUTE TOXICITY:

Eye contact: Vapors may cause eye irritation. Liquid contact may cause tearing, redness, a stinging or burning feeling, swelling, and blurred vision.

<u>Skin contact:</u> May cause effects ranging from mild irritation to severe pain, and possibly burns, depending on the intensity of contact. Skin absorption may occur.

Inhalation: May cause upper respiratory tract irritation and central nervous system depression with symptoms such as confusion, lightheadedness, nausea, vomiting, headache, and fatigue. Causes formation of carbon monoxide in blood which may affect the cardiovascular system and central nervous system. Continued exposure may cause unconsciousness and even death.

Ingestion: May cause nausea or vomiting. If vomiting results in aspiration, chemical pneumonia could occur. Absorption through the gastrointestinal tract may produce central nervous system depression, carboxyhemoglobin, metabolic acidosis and electrolyte disorders, hypotension, cardiac rhythm disorders and seizures.

CHRONIC TOXICITY:

Liver effects have not been reported in humans, but liver changes have been observed in several long-term studies with laboratory animals. Inhalation of 500 to 3,500 ppm methylene chloride for two years produced only minimal, non-proliferative changes in the liver of Sprague Dawley rats (the no-observed-effect level was equal to 200 ppm) and no liver effects in hamsters. Non-proliferative changes were noted in rats in another study after exposure to 1,000 to 4,000 ppm. Liver enlargement has been observed in mice exposed to 2,000 and 4,000 ppm of methylene chloride for 11 days.

Chronic Effects: May cause liver damage. May cause cancer based on animal data. Suspected of causing genetic defects.

SIGNS AND SYMPTOMS OF EXPOSURE:

Inhalation (Breathing): Respiratory System Effects: Pulmonary irritation, cough, chest discomfort, shortness of breath, headache, euphoria, nausea and vomiting, respiratory irritation. Changes in heart rate, paresthesias, sleepiness and seizures are described. Heavy exposure can result in muscle weakness or hypotonia, syncope, stupor followed by loss of consciousness. Complications include cardiac abnormalities and elevations of carboxyhemoglobin. Coma with respiratory depression may result in death.

<u>Skin:</u> Skin Irritation. Skin exposure may cause intense burning sensation, mild redness and numbness. Severe burns may develop following prolonged exposures. Will remove the natural greases resulting in dryness, cracking

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

and dermatitis. Repeated and/or prolonged skin contact may cause reddening, burning and blisters. **Eye:** Eye Irritation. Mild eye irritation may occur when exposed to vapor. Splash of liquid in the eye can cause conjunctival irritation and burning pain. Prolonged contact can cause severe corneal burns. **Ingestion (Swallowing):** Ingesting this material may cause nausea, vomiting, mucosal irritation with burning sensation. System effects include central nervous system depression, headache, syncope, seizures, and coma. Ingesting concentrated solutions of this material can cause corrosion of the GI tract and perforation. The minimum oral lethal dose is estimated at 0.5 to 5 ml/kg. Lesser amounts may cause significant toxicity.

Interaction with Other Chemicals Which Enhance Toxicity: May potentiate other agents that cause central nervous system (CNS) and respiratory system depression, such as alcohol, opiates.

GHS HEALTH HAZARDS:

GHS: CONTACT HAZARD - SKIN: Category 2 - Causes skin irritation
GHS: CONTACT HAZARD - EYE: Category 2A - Causes serious eye irritation
GHS: ACUTE TOXICITY - ORAL: Category 4 - Harmful if swallowed
GHS: TARGET ORGAN TOXICITY (SINGLE EXPOSURE):
Category 1 - Causes damage to cardiovascular system including elevated carboxyhemoglobin levels
Category 3 - May cause drowsiness or dizziness
GHS: TARGET ORGAN TOXICITY (REPEATED EXPOSURE):
Category 2 - May cause damage to liver through prolonged or repeated exposure
GHS: ASPIRATION HAZARD: Category 2 - May be harmful if swallowed and enters airways
GHS: CARCINOGENICITY: Category 1B - May cause cancer
GHS: GERM CELL MUTAGENICITY: Category 2 - Suspected of causing genetic defects

TOXICITY DATA:

PRODUCT TOXICITY DATA:

LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
950 mg/kg (Rat)	> 2,000 mg/kg (Rat)	76000 mg/m ³ (4 hr-Rat)

COMPONENT TOXICITY DATA: The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given

Component	Oral LD50	Dermal LD50	Inhalation LC50
Methylene chloride (Dichloromethane) 75-09-2	1600 mg/kg (Rat)	>2000 mg/kg (Rat)	53 mg/L (6-h Rat)

EYE IRRITATION/CORROSION: Small increases in corneal thickness and intraocular tension reported after exposure of rabbits to vapors of > 490 ppm methylene chloride were reversible within 2 days after exposure ceased. Following direct eye contact with methylene chloride (0.1 mL), rabbits exhibited inflammation of the conjunctivae and eyelids and increases in corneal thickness and intraocular tension. The effects were reversible within 3 to 9 days. This product is classified as causing serious eye irritation (Category 2) per GHS criteria.

Standard Draize (Eye): Methylene Chloride: 162 mg eyes-rabbit moderate; 10 mg eyes-rabbit mild; 500 mg/24 hour(s) eyes-rabbit mild.

SDS No.: M47007		Rev. Date:	23-Jun-2023
Supersedes Date:	New SDS	Rev. Num.	01

SKIN IRRITATION/CORROSION: In animals, an available guideline study demonstrated that methylene chloride could cause skin irritation in rabbits including severe erythema and oedema with necrosis. The product is classified as cutaneous irritant (Category 2), according to GHS classification criteria.

Standard Draize (Skin): Methylene Chloride: 810 mg/24 hour(s) skin-rabbit severe; 100 mg/24 hour(s) skin-rabbit moderate

SKIN ABSORBENT / DERMAL ROUTE: Yes

Dermal absorption of liquid methylene chloride in mice increased linearly with time at a rate of 0.1 mg/cm2/min. An in-vitro study using pig skin measured the dermal permeability of methylene chloride and estimated permeability coefficients of 8.66 x 10-3 cm/hour for the neat (100%) compound and 3.15 x 10-2 (1%) cm/hour for a 1% solution.

RESPIRATORY OR SKIN SENSITIZATION: Results of two human and one rabbit studies have demonstrated no sensitization reactions. Not classified as a skin or respiratory sensitizer per GHS criteria.

CARCINOGENICITY: The International Agency for Research on Cancer (IARC) concluded that there is sufficient evidence in experimental animals for the carcinogenicity of Methylene Chloride. In the evaluation it was pointed out that mechanistic studies have established a link between glutathione S-transferase-mediated metabolism of Methylene Chloride and its genotoxicity and carcinogenicity in mice. The glutathione-S-transferase (GSTT1) responsible for the metabolism of Methylene Chloride is expressed to significantly greater levels in mouse tissues than in rat, hamster, or human tissues and thus, the available data suggest a plausible mechanism for the development of liver and lung tumors occurring in mice which is assumed to be of less importance in rats and hamsters. No studies with Methylene Chloride in humans have investigated whether GSTT1 polymorphisms are associated with cancer. One study has reported an association between a CYP2E1 polymorphism and non-Hodgkin lymphoma in Methylene Chloride exposed individuals; however, the functional significance of this polymorphism is unknown. Overall, given the extensive evidence for genotoxicity, in association with metabolic pathways that are operative in humans, IARC concluded that the mode of action of the carcinogenesis reported in animals is relevant for humans. In conclusion, although the evidence in humans for the carcinogenicity of Methylene Chloride is limited, the available data on carcinogenicity of Methylene Chloride in experimental animals and the mechanistic information is sufficient to support a classification of Methylene Chloride as carcinogen category 1B.

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure): Exposure in an enclosed or poorly-ventilated area may be very harmful. Methylene chloride can be metabolized to carbon monoxide (CO), which is then very tightly bound to hemoglobin. This complex is called carboxyhemoglobin (COHb) and results in a reduction in the oxygen carrying capacity of the blood and may lead to death by chemical asphyxiation. Formation of COHb is not specific to the heart, brain, and cardiovascular system; thus, are not considered target organs. Since CO binds tightly and specifically to blood, blood would be considered a target organ. In addition, the central nervous system (CNS) should be considered a target organ, and the classification for this endpoint is covered under STOT SE Category 3. In several cases of acute, high-dose exposures in humans, the COHb levels have been low (7.5-13%), supporting the fact that Methylene Chloride has direct anesthetic properties, and the CNS depression is not necessarily linked to the presence of carbon monoxide.

SPECIFIC TARGET ORGAN TOXICITY (Repeated or Prolonged Exposure): Liver effects have not been reported in humans; however, liver changes have been observed in several long-term studies with laboratory animals. Inhalation of 500 to 3500 ppm Methylene Chloride for two years produced only minimal, non-proliferative changes in the liver of Sprague Dawley rats (the no-observed-effect level was equal to 200 ppm) and no liver effects in hamsters. Non-proliferative changes were noted in rats in another study after exposure to 1000 to 4000 ppm. Liver enlargement has been observed in mice exposed to 2000 and 4000 ppm of Methylene Chloride for 11 days. The EPA has calculated an RfD (0.006 mg/kg/day) and RfC (0.06 mg/m³) for Methylene Chloride based upon the critical effect of liver toxicity as demonstrated in oral and inhalation toxicity studies in rats. Several other studies (summarized by

SDS No.: M47007	Rev. Date:	23-Jun-2023
Supersedes Date: New SDS	Rev. Num.	01

SCOEL, 2009) indicate that liver effects are observed in repeated animal studies at doses as low as 88 mg/m³.

GERM CELL/IN-VITRO MUTAGENICITY: In general, in the in-vivo genotoxicity studies available in the literature, the strongest responses were observed in mouse lung and liver, tissues with the greatest rates of GST metabolism and the highest susceptibility to methylene chloride-induced tumors. The available data demonstrated a clear correlation between the observed genotoxicity in- vitro and in-vivo and the activity of GST pathway, but a role of P450 metabolic pathway in the induction of genotoxic effects cannot be ruled out. In conclusion, the available data show evidence of genotoxicity both in-vitro and in-vivo. In particular, it is noted that the effects observed in-vivo were in association with metabolic pathway operative also in humans. On this basis, the classification of category 2 is warranted.

REPRODUCTIVE TOXICITY: The available data do not indicate that methylene chloride causes effects on fertility or fetal development.

DEVELOPMENTAL TOXICITY: May cross the placenta. May be excreted in breast milk; however, there were no indications of neonatal toxicity due to exposure of the parenteral group to Methylene Chloride during gestation and lactation.

ASPIRATION HAZARD: Ingestion of liquid methylene chloride may cause chemical pneumonitis. Category 2 - May be harmful if swallowed and enters airways.

TOXICOKINETICS: Methylene chloride is quickly absorbed through inhalation exposure in humans and animals. Pulmonary uptake ranges between 40 and 60 percent, but may be up to 70 percent during the first minutes of exposure. In humans, uptake decreases as exposure duration and concentration increase. A steady-state absorption rate is generally achieved within 2 hours for exposures up to 200 ppm in humans. Methylene chloride is rapidly distributed throughout the body, including the liver, brain and subcutaneous adipose tissue, as identified in animal studies. Among fatality cases, the highest concentrations were usually found in the brain, then liver or kidneys and finally in the lungs and heart.

METABOLISM: Metabolism occurs predominantly in the liver, with additional transformation in the lungs and kidneys. In the liver, two primary pathways are involved in the metabolism of methylene chloride. The cytochrome P450 (CYP450) mixed function oxidase (MFO) pathway (via CYP2E1) produces CO and CO2, and saturation occurs at approximately 400-500 ppm after inhalation exposure in humans. The CO metabolite reacts with hemoglobin to form carboxyhemoglobin (COHb). The second pathway operates via glutathione S-transferase (GST); individuals with the theta 1 isozyme (GSTT1) metabolize methylene chloride to form formaldehyde and formic acid. In animals, saturation occurs at >10,000 ppm after inhalation exposure. Methylene chloride binds to the CYP reaction site with higher affinity than the GST site and COHb levels resulting from methylene chloride's metabolism to CO can continue to increase and can reach peak levels 5 to 6 hours after exposure. The plasma half-life is estimated to be 40 minutes after inhalation exposure by human subjects. Unmetabolized methylene chloride is eliminated primarily through the lungs. Urine and feces also contain small quantities of unchanged methylene chloride. At low doses, a large percent of methylene chloride is transformed into COHb and eliminated as CO. At higher doses, more of the unchanged parent compound is exhaled.

ENDOCRINE DISRUPTOR: Methylene chloride is listed on The Endocrine Disruptors Exchange's (TEDX) List of Potential Endocrine Disruptors (ED) database of chemicals with the potential to affect the endocrine system. Every chemical on the TEDX List has one or more verified citations published, accessible, primary scientific research demonstrating effects on the endocrine system. Literature data concerning reproductive/developmental effects points out directly to a potential ED-like mode of action. In particular, taking into account both: i) the CYP-mediated mechanism(s) supporting both hepatic and biliary tract carcinogenesis alert at low dichloromethane doses, and ii) the CYP2E1-mediated mechanism supporting the reproductive/developmental alert in the male germ line, a concern on the possibility that dichloromethane could act via an ED-like mechanism exists. A study (Mennear JH et al., 1988) on

23-Jun-2023

01

SDS No.: M47007	Rev. Date:
Supersedes Date: New SDS	Rev. Num.

dichloromethane-mediated carcinogenesis in F344/N rats indicated that a set of endocrine-regulated tissues (mammary glands, testis, adrenals) were responding, in a non-linear dose-dependent manner, to the treatment with dichloromethane, suggesting a possible relationship with disturbed endocrine function and raising the possibility of a hormonal-mediated mechanism(s) at a realistic scenario of exposure to humans.

NEUROTOXICITY: Nervous system effects related to methylene chloride exposure include effects related to CNS depression in humans as well as spontaneous activity and other effects in animals. Developmental neurotoxicity has also been observed in human studies and a limited number of animal studies.

IMMUNOTOXICITY: There is some evidence to support immune system effects following methylene chloride exposure, but data are sparse with an apparent lack of consistency.

Health Hazards of Significance Not Mentioned in GHS Classification

• Methylene chloride can be metabolized to carbon monoxide (CO), which is then very tightly bound to hemoglobin. This complex is called carboxyhemoglobin (COHb) and results in a reduction in the oxygen carrying capacity of the blood

• Exposure in an enclosed or poorly ventilated area may be very harmful

• May cross the placenta. May be excreted in breast milk; however, there were no indications of neonatal toxicity due to exposure of the parenteral group to Methylene Chloride during gestation and lactation.

• This material may be absorbed across the skin causing systemic effects

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICITY (EC, IC, and LC):

Ecotoxicity - Available LOLI Data for Components: As noted in table below: Component: Freshwater Fish: Invertebrate Algae Toxicity: Other Toxicity: Toxicity: *EC50 Daphnia *EC50 Methylene chloride *LC50 Pimephales LC50 Eisenia foetida (Dichloromethane) promelas: 140.8 magna: 1532 - 1847 Pseudokirchneriella (48 h filter paper) 75-09-2 (> 99.99 %) 277.8 mg/L 96h mg/L 48h *EC50 =0.3 mg/cm2 *LC50 subcapitata (96 h) flow-through *LC50 >500 mg/L Eisenia foetida (48 h Daphnia magna: 190 Pimephales *EC50 mg/L 48h filter paper) =304 promelas: 262 - 855 Pseudokirchneriella mg/cm2 mg/L 96h static subcapitata (72 h) *LC50 Lepomis >500 mg/L macrochirus: 193 mg/L 96h flow-through *LC50 Lepomis macrochirus: 193 mg/L 96h static

Aquatic Toxicity:

The acute effect concentrations of methylene chloride for all three trophic levels exceed the screening criterion of 100 mg/L. It can therefore be considered that methylene chloride is not acutely toxic towards aquatic organisms
For rapidly biodegradable substances, chronic NOEC values above 1 mg/L and/or acute LC50 values above 100 mg/L do not result in classification. Since it was highly volatile and diffused rapidly into the air, and the bioaccumulation was low, it was not classified for chronic aquatic toxicity

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

Fish Toxicity:

LC50 (Static) Fathead minnow = 310 mg/L (96 hr) LC50 (Static) Bluegill sunfish = 220 mg/L (96 hr)

Invertebrate Toxicity:

LC50 Mysid Shrimp = 256 mg/L 96 hour(s) 224 mg/L 48 hour(s) LC50 Daphnia Magna

FATE AND TRANSPORT:

PERSISTENCE: Due to its high Henry's Law constant and vapor pressure (435 mmHg at 25°C), methylene chloride is expected to volatilize from surface water and soil. The EPI Suite[™] module that estimates volatilization from lakes and rivers (water volatilization model) was run using default settings to evaluate the volatilization half-life of methylene chloride in surface water and estimated that the half-life of methylene chloride in a model river will be 1.1 hours and the half-life in a model lake will be less than 4 days. In the atmosphere, methylene chloride will slowly react with hydroxyl radicals (•OH), with an indirect photolysis half-life of 79 days. Due to its persistence, methylene chloride is expected to be subject to local and long-range atmospheric transport. Based on its vapor density (2.93 relative to air), volatilized methylene chloride is expected to remain near ground level in very calm conditions, but with mixing will readily disperse into the air.

BIODEGRADATION: Methylene chloride will not rapidly biodegrade in aerobic environments. Overall, methylene chloride biodegradation rates in aerobic environments may vary based on factors including microorganism consortia present and microorganisms' previous exposure and adaptation to methylene chloride or other halogenated substances. In agreement with the experimental data for anaerobic biodegradation of methylene chloride, the BIOWIN model of anaerobic biodegradation (BIOWIN 7) predicts that methylene chloride will biodegrade rapidly under anaerobic conditions.

BIOCONCENTRATION: Bioconcentration potential in aquatic organisms is low with BCF of 2.

BIOACCUMULATIVE POTENTIAL: The bioconcentration potential of methylene chloride is low; the EPI Suite[™] BCFBAF model estimates bioconcentration factors of 2.6 to 3.1 and a bioaccumulation factor of 2.6. Based on these estimated bioconcentration factor and bioaccumulation potential, methylene chloride does not bioaccumulate in biological organisms.

MOBILITY IN SOIL: Methylene chloride is not expected to partition to or accumulate in soil; rather, it is expected to volatilize to air or migrate through soil into groundwater based on its physical-chemical properties (log KOC = 1.4, Henry's Law constant = 0.00325 atm-m3 /mole, vapor pressure = 435 mmHg at 25°C).

PBT and vPvB assessment: The overall conclusions - based on the available data under EU REACH registration- of the preliminary PBT assessment are that the (screening) criteria for PBT/vPvB are not met and that further testing in the scope of the final PBT assessment is not considered to be required.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from material:

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

Reuse or reprocess, if possible. Keep out of water supplies, sewers, and soil. Small spills should be absorbed with a compatible absorbent material and placed in clean, dry stainless steel drum to offer for disposal. Incineration is the preferred method for disposal of large quantities by mixing with a combustible solvent and spraying into an incinerator equipped with acid scrubbers to remove hydrogen chloride gases formed. Complete combustion will convert carbon monoxide to carbon dioxide. Care should be taken for the presence of phosgene. Dispose in accordance with all applicable regulations. Generators of waste (equal to or greater than 100 kg/mo) containing this contaminant, EPA hazardous waste numbers U080 and F002, must conform with USEPA regulations in storage, transportation, treatment and disposal of waste.

Container Management:

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

Contaminated Material:

Wastewater from contaminant suppression, cleaning of protective clothing/equipment, or contaminated sites should be contained and evaluated for subject chemical or decomposition product concentrations. Concentrations shall be lower than applicable environmental discharge or disposal criteria. Alternatively, pretreatment and/or discharge to a permitted wastewater treatment facility is acceptable only after review by the governing authority and assurance that "pass through" violations will not occur. Consideration to the potential exposure(s) to remediation workers should be evaluated (inhalation, dermal, and ingestion) and controlled. In addition, all generators must determine if their waste is hazardous and must oversee the ultimate fate of the waste during treatment, transfer, and disposal. If it is not practicable to manage the chemical in this fashion, it must be evaluated in accordance with EPA 40 CFR Part 261, specifically Subpart B, in order to determine the appropriate local, state, and federal requirements for disposal. Potential candidate for liquid injection incineration, with a temperature range of 650 to 1600°C and a residence time of 0.1 to 2 seconds; for rotary kiln incineration with a temperature range of 820 to 1600°C and residence times of seconds for liquids and gases, hours for solids; and for fluidized bed incineration, with a temperature range of 450 to 980°C and residence times of seconds for liquids and gases, longer for solids.

SECTION 14. TRANSPORT INFORMATION

LAND TRANSPORT

U.S. DOT 49 CFR 172.101:	
UN NUMBER:	UN1593
PROPER SHIPPING NAME:	Dichloromethane
HAZARD CLASS/ DIVISION:	6.1
PACKING GROUP:	III
LABELING REQUIREMENTS:	6.1
RQ (Lbs.):	RQ 1,000 Lbs. (Dichloromethane)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS: UN NUMBER: UN1593

SHIPPING NAME:DichloromethaneCLASS OR DIVISION:6.1PACKING/RISK GROUP:III

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

LABELING REQUIREMENTS: 6.1

MARITIME TRANSPORT (IMO / IMDG)

UN NUMBER:UN1593PROPER SHIPPING NAME:DichloromethaneHAZARD CLASS / DIVISION:6.1Packing Group:IIILABELING REQUIREMENTS:6.1MARINE POLLUTANT:No

AIR TRANSPORT (ICAO / IATA)

UN Number:	See 14.6
Proper shipping name:	See 14.6
Hazard Class:	See 14.6
Packing group:	See 14.6
Special Instructions CAO:	IATA Certificate for shipping personnel is required

SECTION 15. REGULATORY INFORMATION

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

Regulated as noted in table below.

Component	U.S. DOT Hazardous	CERCLA Hazardous	CERCLA Section 302	Section 302 Threshold
	Substances/ RQs	Substances / RQs	EHS EPCRA RQs	Planning Quantity (TPQ)
Methylene chloride (Dichloromethane) 75-09-2 (> 99.99 %)	1000 lbs(RQ)	1000 lb	Not listed	Not Listed

SARA EHS Chemical (40 CFR 355.30)

If a release is reportable under EPCRA, notify the state emergency response commission and local emergency planning committee. If the TPQ is met, facilities are subject to reporting requirements under EPCRA Sections 311 and 312.

Acute Health Hazard, Chronic Health Hazard

SARA HAZARD CATEGORIES ALIGNED WITH GHS (2018):

Health Hazard - Carcinogen

Health Hazard - Germ Cell Mutagenicity

Health Hazard - Acute Toxin (any route of exposure)

Health Hazard - Skin Corrosion or Irritation

Health Hazard - Serious eye damage or eye irritation

Health Hazard - Specific Target Organ Toxicity (STOT) Single Exposure (SE)

Health Hazard - Specific Target Organ Toxicity (STOT) Repeat Exposure (RE)

SDS No.: M47007 Supersedes Date: New SDS Rev. Date: 23-Jun-2023 Rev. Num. 01

Health Hazard - Aspiration Hazard Health Hazard - HNOC

EPCRA SECTION 313 (40 CFR 372.65):

The following chemicals are listed in 40 CFR 372.65 and may be subject to Community Right-to Know Reporting requirements.

Component	SARA 313 - Emission Reporting	SARA 313 PBT	
Methylene chloride (Dichloromethane)	0.1% (de minimis concentration)	Not Listed	
75-09-2 (> 99.99)			

DEPARTMENT OF HOMELAND SECURITY (DHS)- Chemical Facility Anti-Terrorism Standards (6 CFR 27): No components in this material are regulated under DHS

OSHA SPECIFICALLY REGULATED SUBSTANCES:

OSHA 29 CFR 1910.1052 (Methylene chloride); The U.S. Department of Labor, Occupational Safety and Health Administration specifically regulates manufacturing, handling and processing of methylene chloride. Such regulations have been published at 29 CFR 1910.1052.

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated.

Component	EPA RMP Toxic or Flammable TPQ	PSM - Highly Hazardous Substances, Toxics and Reactives	Flash Point
Stabilizer 1 (0.00005 - 0.0001)	Not Listed	Not Listed	<-7°C

FDA: This material is not a Food Grade material, and as such does not meet the FDA's Food Safety Modernization Act (FSMA) requirements, and is not guaranteed to be produced under all current Good Manufacturing Practices (cGMP) requirements as defined by the FDA. This material has Generally Recognized As Safe (GRAS) status under specific U.S. Food and Drug Administration (FDA) regulations. Additional information is available from the Code of Federal Regulations, which is accessible on the FDA's website.

EPA'S CLEAN WATER AND CLEAN AIR ACTS:

Regulated as noted in table below.

Component	Clean Water Act - Priority Pollutants	CAA - ODS CLASS 1 AND CLASS 2	CAA - Volatile Organic Compounds (VOCs) in SOCMI	CAA - HON Rule - Organic HAPs	CAA - Hazard Air Pollutants	CAA - Urban HAPs List (Integrated Urban Strategy)	SNAP - Substitutes for ODS	EPA RMP Toxic or Flammable TPQ
Methylene chloride (Dichloromethane) 75-09-2 (> 99.99 %)	Present	Not Listed	Present	Present	Present	Present	Not Listed	Not Listed
Stabilizer 1 (0.00005 - 0.0001 %)	Not Listed	Not Listed	Present	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA):

Component 1	TSCA Inventory	TSCA ACTIVE LIST	TSCA 12(b)	TSCA/Section 4	TSCA/Section 5	TSCA/Section 6	TSCA/Section 8
Methylene chloride (Dichloromethane)	Listed	ACTIVE R	Section 6 (0.1 %)	Not listed	Not Listed	Chemicals subject to Risk	Listed

SDS No.: M47007

Supersedes Date: New SDS

Rev. Date: 23-Jun-2023 **Rev. Num.** 01

75-09-2 (> 99.99 %)						Evaluation	
Stabilizer 1	Listed	ACTIVE	Not Listed	Not listed	Not Listed	Not Listed	Listed
(0.00005 - 0.0001 %)							

Toxic Substance Control Act (TSCA) Restriction of Use:

- This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal

- (R) Indicates a substance that is the subject of a TSCA Section 6 risk management rule

TSCA 12(b): Methylene Chloride is subject to TSCA 12(b) annual reporting requirements (per country) De minimis reporting level: 0.1%

TSCA Section(s): 6(a).

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

Component	DSL	NDSL
Methylene chloride (Dichloromethane)	Listed	Not Listed
75-09-2 (> 99.99)		
Stabilizer 1	Listed	Not Listed
(0.00005 - 0.0001)		

STATE REGULATIONS

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer, and/or birth defects, and/or other reproductive harm as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act.

Component	U.S California - Proposition 65 - Carcinogens List	CA. Prop. 65 Teratogen	California Proposition 65 CRT List - Male reproductive toxin:	California Proposition 65 CRT List - Female reproductive toxin:	Massachusetts Right to Know Hazardous Substance List	Rhode Island Right to Know Hazardous Substance List
Methylene chloride (Dichloromethane) 75-09-2 (> 99.99 %)	Listed	Not listed	Not Listed	Not Listed	Listed	Listed
Stabilizer 1 (0.00005 - 0.0001 %)	Not listed	Not listed	Not Listed	Not Listed	Listed	Listed

Component	New Jersey Right to Know Hazardous Substance List	New Jersey Special Health Hazards Substance List	New Jersey - Environmental Hazardous Substance List	Pennsylvania Right to Know Hazardous Substance List	Pennsylvania Right to Know Special Hazardous Substances	Pennsylvania Right to Know Special Hazardous Substances	Pennsylvania Right to Know Environmental Hazard List
Methylene chloride (Dichloromethane)	1255	Not Listed	Listed	Listed	Present	Present	Present
Stabilizer 1	0572	Not Listed	Not Listed	Listed	Not Listed	Not Listed	Not Listed

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Workplace Hazardous Materials Information System (WHMIS 2015) which includes the amended Hazardous Products Act (HPA) and the Hazardous Product Regulations (HPR).

Component Canada - CEPA - Schedule I - List of Toxic Substances	Canada - NPRI	Canada - CEPA - Greenhouse Gases (GHG) Subject to	Canadian Chemical Inventory:	NDSL
---	---------------	---	---------------------------------	------

SDS No.: M47007 Supersedes Date: New SDS **Rev. Date:** 23-Jun-2023 **Rev. Num.** 01

			Mandatory Reporting		
Methylene chloride (Dichloromethane) 75-09-2 (> 99.99)	Present (037)	Part 1, Group A Substance (065)	Not Listed	Listed	Not Listed
Stabilizer 1 (0.00005 - 0.0001)	Present (065)	Part 5 Substance - Volatile Organic Compounds with Additional Reporting Requirements (270)	Not Listed	Listed	Not Listed

SECTION 16. OTHER INFORMATION

Prepared by: Occidental Chemical Corporation - HES&S Product Stewardship Department

Rev. Date: 23-Jun-2023

Reason for Revision:

Scheduled review

• The SDS for this grade of product has been separated from the Technical Grade and other grade products due to variation in stabilizer(s)

• Updated information based upon review of EPA's final Risk Evaluation

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any federal, state, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees.

End of Safety Data Sheet