



Sales Specification

Perchloroethylene (C₂Cl₄)

Isomerization Grade

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Perchloroethylene, wt. %	99.99 min.
Color, APHA	10 max.
Appearance (ASTM D3741-B)	Passes Test
Acidity, ppm as HCl	5 max.
Specific Gravity @ 25/25°C	1.617 - 1.621
Nonvolatile Residue, ppm	10 max.
Water, ppm	25 max.
Free Halogens, (ASTM D 4755)	Passes Test
Chlorides, ppm	1 max.
Stabilizer, ppm	10 max.
Organically Combined Oxygen plus Organically Combined Nitrogen, ppm	15 max.

Reviewed and approved by UOP for use in isomerization processes.

CONTAINERS:

Tank Cars - Lined 20,000-gallon cars and maximum weight load of 197,000 lbs.

Tank Trucks (stainless) - Shell capacity or maximum weight load of 3,600 gallons

Drums - 700-pound net, 747-pound gross weight drums, UN 1A1/Y1.8/300

Form#: 584 04/2022



14555 Dallas Parkway, Suite 400
Dallas, TX 75254
800-752-5151

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.