



Product Transfer System Design Considerations For Top Unloaded Solvent Tankcars

Features of OxyChem's Top Unloaded Solvent Tank Cars

- No Bottom Outlets
- 20,000 Gallon Normal Capacity (at 2% outage)

All Valves are Mounted in a Protective Housing on Top of the Tankcar, Including:

- 3" Liquid Unloading Valve
- 3" Air/Vapor Return Valve
- 150 psig Safety Relief Valve
- ¾" Sampling Valve

Product Transfer System

Design Considerations

A. Self Priming Pump

For utilization of a pump to transfer product from a top unloaded tank car it must be capable of priming itself. The pump specification must take into consideration that solvents are heavy and have relatively high vapor pressures (see Table 1 for density, viscosity, and vapor pressure curves). An improperly designed pump will not be capable of maintaining a prime, and will either be unable to transfer product, or do so with reduced performance.

B. Non Self-Priming Pump Transfers

Facilities which have pumps without a built-in priming chamber can upgrade the pump by installing a priming reservoir with a capacity of at least 25% greater volume than the volume of the suction hose used in the transfer. Reservoirs should be permanently secured to the pumping station and elevated above the pump suction port. The reservoir is typically top-filled by a ½ inch supply line connected to the suction hose. Discharge is transferred from the bottom of the reservoir to the suction port of the pump by a ½ inch pipe, typically. In this design, the reservoir should be able to withstand the Net Positive Suction Head (NPSH) expected from the pump upon start-up and should be affixed with a pressure and vacuum relief device.

In the event the pump requires service, block valves should be installed on the reservoir's discharge line, as well as a double block and bleed valve arrangement on the suction line supplying the reservoir and pump inlet. With the exception of the

bleed valve, all valves should be opened before start-up and closed immediately upon completion of the product transfer.

Pump transfers will allow the vapors displaced in the receiving tank to be returned to the tank car (the concept of vapor balancing).

If vapor balancing is not employed, the tank car must be vented during unloading.

C. Compressed Gas Transfers

The method of applying a moderate pressure to the tank car to displace product out of the container is perhaps the most economical transfer method. Typically, an inert gas such as air or nitrogen is employed. The compressed gas system should have enough capacity to transfer product at the desired rate, which will be determined by the hydraulics of the unloading station. Typical compressed gas transfer systems employ pressures below 20 psig. A pressure relief valve set at 25 psig maximum, and pressure gauges must be installed to regulate and monitor safe compressed gas pressures.

This method of transfer may introduce contaminants into the product if the air pressure system is not designed to remove moisture and oil.

Because pressure is applied to the tankcar, the vapors displaced in the receiving tank cannot be returned to the tankcar.

A surge of air/nitrogen pressure may occur through the transfer system and receiving tank when the tankcar goes empty.

OxyChem requires pressure to be removed from the tankcar before returning it to our shipping point due to safety considerations.

D. Pump Assisted with Air/Nitrogen Pressure

To maintain the prime on a pump it may be necessary to apply a slight pressure to the tankcar.

A ¾" or 1" bypass line with block valve between the suction and discharge line is necessary to allow the suction hose to fill with liquid and the vapor/air in the suction hose to pass to the discharge line. This operation should take place before starting the

pump. Once pumping has begun, the bypass line valve should be closed.

This method of transfer may introduce contaminants to the product if the air pressure system is not designed to remove moisture and oil.

Because pressure is applied to the tankcar the vapors displaced in the receiving tank cannot be returned to the tankcar.

A surge of air/nitrogen pressure may occur through the transfer system and receiving tank when the tankcar goes empty.

OxyChem requires pressure to be removed from the tankcar before returning our shipping point due to safety considerations.

Table 1 - Solvent Physical Properties

Solvent	Specific Gravity @ 25/25 °C	Vapor Pressure @ 20 °C, mm Hg	Liquid Viscosity @ 20 °C, cP
Carbon Tetrachloride	1.59	91	0.97
Chloroform	1.48	160	0.57
Ethylene Dichloride	1.25	62	0.84
Methylene Chloride	1.32	350	0.43
Perchloroethylene	1.62	13	0.88
Solvent 111®	1.32	100	0.86
Trichloroethylene	1.45	58	0.58

Equipment Suppliers

The following vendors are known to sell equipment that may be needed in a product transfer system. This list is not all-inclusive and is not necessarily an endorsement of these companies.

Pumps

Goulds Pumps (315) 568-2811
The Duriron Co., Pump Division (513) 226-4000

Air Compressors

Atlas Copco (413) 536-0600
Gardner Denver Machinery (800) 682-9868
Sulair Corp. (800) 785-5247

Load Racks

HEMCO Industries (713) 681-2426
H&P Systems (713) 937-4421
Carbis Sales (803) 669-6668

Further Information

More detailed information on transferring solvents is available upon request through the OxyChem Technical Service Department. Call or write to:

Technical Service Department
OxyChem
Post Office Box 12283
Wichita, Kansas 67277-2283
800-733-1165
www.oxy.com

Important! The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. No warranty or guaranty, express or implied, is made regarding performance, stability or otherwise. This information is not intended to be all-inclusive as the manner and conditions of use, handling storage and other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any Federal, State or local laws.