



Responsible Care
Good Chemistry at Work

OxyChem® A subsidiary of Occidental Petroleum Corporation

Ethylene Dichloride

(1,2 Dichloroethane, C₂H₄Cl₂)

TECHNICAL GRADE

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Appearance	Clear
Ethylene Dichloride, wt%	99.8 min.
Specific Gravity, 25/25°C	1.249 - 1.252
Color, APHA	10 max.
Acidity, ppm as HCl	2 max.
Alkalinity, ppm as NaOH	2 max.
Nonvolatile Matter, ppm	10 max.
Water, ppm	100 max.
Free Halogens (ASTM D 4755)	Passes Test
Soluble Iron, ppm as Fe	5 max.
Chloral, ppm	50 max.

TYPICAL PROPERTIES

Distillation Range, 760 mm, °C	82.5 - 84.5
Heavy Metals, ppm as Pb	1 max.

Typical properties are listed for information only, and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

Meets Military Specification MIL-D-10662-D (replaced by ASTM D 5960-03)

Meets requirements of ASTM Specification D 5960-03

Meets test requirements of the *Food Chemicals Codex*, sixth Edition

Meets test requirements for General Use Ethylene Dichloride in *ACS Specifications for Reagent Chemicals*, 10th Edition, 2006

CONTAINERS:

Tank Cars - Lined 20,000 gallon cars and maximum weight load of 197,000 lbs.

Drums - 565 pound net, 615 pound weight drums, 18 gauge, nonreturnable UN 1A1/Y1.8/300



Occidental Chemical Corporation
Basic Chemicals Group
Occidental Tower
5005 LBJ Freeway
Dallas, TX 75244
800-752-5151

Important! The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. No warranty or guaranty, expressed or implied, is made regarding performance, stability or otherwise. This information is not intended to be all-inclusive as the manner and conditions of use, handling storage and other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any Federal, State or local laws.