



Responsible Care
Good Chemistry at Work

OxyChem® A subsidiary of Occidental Petroleum Corporation

20° Bé Muriatic Acid (HCl)

TECHNICAL GRADE

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Assay, °Baumé	20.0 min.
Hydrogen Chloride, wt.% as HCl	31.45 min.
Iron, ppm as Fe	3 max.
Heavy Metals as Pb, ppm	1 max.
Arsenic, ppm as As	0.5 max.
Oxidizing Substances, ppm as Cl ₂	10 max.
Color, APHA	30 max.
Extractable Organic Compounds	
Total Organic Compounds (Non-Fluorine-Containing), ppm	5 max.
Fluorinated Organic Compounds, ppm	25 max.

Meets test requirements of the *Food Chemicals Codex*, sixth Edition
Meets Federal Specification O-H-765E (replaced by ASTM E 1146-97)
Meets requirements of ASTM E 1146-08

CONTAINERS:

Tank Cars - 20,000 gallon, rubber lined
Tank Trucks - 4,500 and 5,000 gallon, rubber lined



Occidental Chemical Corporation
Basic Chemicals Group
Occidental Tower
5005 LBJ Freeway
Dallas, TX 75244
800-752-5151

Important! The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. No warranty or guaranty, expressed or implied, is made regarding performance, stability or otherwise. This information is not intended to be all-inclusive as the manner and conditions of use, handling storage and other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any Federal, State or local laws.

09/09

Form No.: 112