

Sales Specification

Sodium Chlorite (NaClO₂)

Textone® XL

COMPONENT

Sodium Chlorite, wt% as NaClO₂ Sodium Chlorate, wt% as NaClO₃ Sodium Chloride, wt% as NaCl Total Alkalinity as NaOH @ pH4, wt% Hydrogen Peroxide, wt% as H₂O₂ Water (by difference), wt%

SPECIFICATIONS

30.5 - 31.5 0.5 max. 3.5 max. 1.0 max. 0.01 max. 61 - 69.5

TYPICAL PROPERTIES

Appearance Clear, slightly yellow liquid Turbidity, NTU 15 Max Density, lb/gal @ 25°C 10.6 Typical properties are listed for information only and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

<u>CONTAINERS:</u> Tank Cars (fiberglass lined)-16,000 gallons Tank Trucks (stainless steel) - 4000 gallons Drums - 55 Gallon Plastic Drums OCC non-returnable 330-gallon tote with steel box and plastic bottle

Form#: 631 05/2019

14555 Dallas Parkway, Suite 400 Dallas, TX 75254 800-221-6514 Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

