



Calcium Chloride Products



SALES SPECIFICATION

PELADOW™ DG Calcium Chloride

<u>Property</u>	<u>Minimum</u>	<u>Maximum</u>
Calcium Chloride (wt. %)	88	93
Retained on 1/2 in. (12.7 mm) sieve (wt. %)	89	
Passing 1/4 in. (6.35 mm) sieve (wt. %)		3

Effective: 10/01/2009

Reviewed: 09/25/2017

Material description: white, odorless briquettes

Typical bulk density is 60 – 68 lb/ft³

SS-DGD Sep 2017



5005 LBJ Freeway
Dallas, Texas 75244-6119
800-752-5151

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.