



Responsible Care
Good Chemistry at Work

OxyVinyls LP® A Subsidiary of Occidental Petroleum Corporation

Vinyl Chloride Monomer (VCM) Specifications

Parameter	Units	Minimum	Maximum
VCM Purity	% wt.	99.98	
Water	ppm wt.		100.0
Acidity (HCl)	ppm wt.		1.0
Iron	ppm wt.		0.40
Non-Volatile Residue	ppm wt.		50.0
1,3-Butadiene	ppm wt.		8.0
Acetylene	ppm wt.		0.40
Methyl Chloride	ppm wt.		60.0
Vinyl Acetylene	ppm wt.		15.0
Total Hi Boilers (Heavy Ends)	ppm wt.		50.0
Appearance	Clear, Colorless, Free of Suspended Matter		

Oxy Vinyls, LP
April 2013



OxyVinyls, LP
5005 LBJ Freeway
Dallas, Texas 75244
877-699-8465

Important! The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. No warranty or guaranty, express or implied, is made regarding performance, stability or otherwise. This information is not intended to be all-inclusive as the manner and conditions of use, handling storage and other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or to violate any Federal, State or local laws.