



Sales Specification

Ethylene Dichloride (C₂H₄Cl₂)

(1,2-Dichloroethane)

Technical Grade

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Appearance	Clear
Ethylene Dichloride, wt%	99.8 min.
Specific Gravity, 25/25°C	1.249 - 1.252
Color, APHA	10 max.
Acidity, ppm as HCl	2 max.
Alkalinity, ppm as NaOH	2 max.
Nonvolatile Residue, ppm	10 max.
Water, ppm	100 max.
Free Halogens (ASTM D 4755)	Passes Test
Soluble Iron, ppm as Fe	5 max.
Chloral, ppm	50 max.

TYPICAL PROPERTIES

Distillation Range, 760 mm, °C	82.5 - 84.5
Heavy Metals, ppm as Pb	1 max.

Typical properties are listed for information only and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

Meets Military Specification MIL-D-10662-D (replaced by ASTM D5960-03)

Meets requirements of ASTM Specification D5960-03

Meets test requirements of the *Food Chemicals Codex*, 13th Edition

Meets test requirements for General Use Ethylene Dichloride in *ACS Specifications for Reagent Chemicals*, Online Edition, Current version date 6/1/2016

This product is not produced under all cGMP requirements as defined by the FDA.

CONTAINERS:

Tank Cars - Lined 20,000-gallon cars and maximum weight load of 197,000 lbs.

Drums - 565-pound net, 615- pound gross weight drums, nonreturnable UN 1A1/Y1.8/300

Form#: 551 08/2022



14555 Dallas Parkway, Suite 400
Dallas, TX 75254
800-752-5151

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.