



Sales Specification

Perchloroethylene (C₂Cl₄)

Industrial Grade

COMPONENT SPECIFICATIONS

Color, APHA
Specific Gravity @ 25/25°C
Nonvolatile Residue, ppm
Water, ppm
Free Halogens (ASTM D 4755)

15 max. 1.617 - 1.621 10 max. 30 max. Passes Test

TYPICAL PROPERTIES

Distillation Range, 760 mm, °C

120.6 - 121.6


Form#: 581

08/2022

Typical properties are listed for information only and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

CONTAINERS:

Tank Cars - Lined 20,000-gallon cars and maximum weight load of 197,000 lbs. Tank Trucks (stainless) - Shell capacity or maximum weight load of 3,600 gallons Drums - 700-pound net, 740-pound gross weight drums, UN 1A1/Y1.8/300



Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal, and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.