



## Sales Specification

# Sodium Chlorite (NaClO<sub>2</sub>)

### AktaKlor 25

(25% Active Sodium Chlorite)

| COMPONENT   | <b>SPECIFICATIONS</b> |
|---|-----------------------|
| Sodium Chlorite, wt% as NaClO <sub>2</sub>              | 24.25 - 25.75         |
| Sodium Chlorate, wt% as NaClO <sub>3</sub>              | 0.5 max.              |
| Sodium Chloride, wt% as NaCl                            | 3.0 max.              |
| Total Alkalinity, wt% as NaOH @ pH4                     | 0.5 max.              |
| Hydrogen Peroxide, wt% as H <sub>2</sub> O <sub>2</sub> | 0.01 max.             |
| Water (by difference), wt%                              | 68 - 76               |

### TYPICAL PROPERTIES

Appearance Clear, slightly yellow liquid Turbidity, NTU 10 max Density, lb/gal @ 25°C 10.1

Typical properties are listed for information only and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

NSF Listed, ANSI/NSF Standard 60 (Wichita, KS/Fairmont City, IL) Meets requirements of ANSI/AWWA B303-24

EPA Reg. No: 21164-6

#### **CONTAINERS:**

Tank Cars (fiberglass lined)-16,000 gallons
Tank Trucks (stainless steel)-3400 gallons
Drums-55 Gallon Plastic Drums, 565 lbs net
OCC non-returnable 330-gallon tote with steel box and plastic bottle



